

Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Revision Date: 04.08.2022 Version 2

TEKKİM

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalog No. TK.050140.00000
Product Name Ethyl Acetate
Cas no 141-78-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial use. Use as a laboratory reagent.

1.2.2. Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Name TEKKİM KİMYA SAN. TİC. LTD. ŞTİ.
Street ORGANİZE SAN. BÖL. MAVİ CAD. 8. SOK. NO :1 NİLÜFER / BURSA
Telephone 0224 243 21 71
E-mail erhan@tekkim.com.tr
Company Representative Erhan DİLER

1.4 Emergency Telephone Number +90 506 990 36 86

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Flammable liquid category 2

Eye irritation category 2

Specific Target Organ Toxicity - Single exposure (Category 1), Central nervous system

For the full text of the H and EUH statements referred to in this section, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictograms



Signal word (SEA)

DANGER

Hazard Statements (SEA)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements (SEA)

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.

P233 Keep container tightly closed.

P240 Ground/connect container or receiving equipment.

P241 Use explosion-proof electrical/ventilation/igniter/.../ material.


P242 Use only non-flammable tools.

Intervention

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if fitted and easy to do. Continue rinsing.



Tekkim is accredited to
ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an  group company
www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Caddesi 8.Sokak No:1 Nilüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

+90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Revision Date: 04.08.2022 Version 2

TEKKİM

SECTION 3: Composition/information on ingredients

Classification according to Regulation (EC) No. 1272/2008 (CLP)

3.1 Maddeler

EC No	205-500-4
Molar mass	88.11 g/mol
Cas No	141-78-6
Concentration	(<= 100 %)

SECTION 4: First aid measures

4.1 Description of first aid measures

<i>General information</i>	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
<i>Following inhalation</i>	Remove casualty to fresh air and keep warm and at rest..
<i>Following skin contact</i>	Wash with plenty of water. Take off contaminated clothing.
<i>Following eye contact</i>	In case of contact with eyes, rinse immediately with plenty of water and consult an ophthalmologist.
<i>Following ingestion</i>	Give up to two glasses of water. Get medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

There is no restriction for this item.

5.2 Special hazards arising from the substance or mixture

Carbon oxides. Flammable. Heavy vapors in the air at the ground surface may occur. It can create explosive mixtures with air on intense heating. In case of fire hazardous combustion gases or vapors may occur. Flashback. Caution.

5.3 Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus..

5.4 Additional information

Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Don't breathe vapours, aerosols. Avoid substance contact. Keep away from head and source of ignition. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert..

6.2 Environmental precautions

Be careful not to mix into the sewer. Risk of explosion.

6.3 Methods and material for containment and cleaning up

Close drainage channels. Take up with liquid-absorbent material. Clean the affected area.

6.4 Reference to other sections

Disposal: see section 13.



Tekkim is accredited to
ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an group company
www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Caddesi 8.Sokak No:1 Nilüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

+90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Revision Date: 04.08.2022 Version 2

TEKKİM

6.5 Additional information

Clear spills immediately.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Advices on safe handling

Observe label precautions. Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advices on general occupational hygiene

Change contaminated clothing. Wash hands after working with substance. It is recommended to use a skin protection cream

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in dry and well-ventilated places. Protect from light. Keep away from heat and anything that can cause ignition.

7.3 Specific end uses

There are no other specific uses other than those mentioned in section 1.2.

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ethyl acetate (141-78-6)

TR MAK Time Weighted Average (TWA): 400 mbp
1.400 mg / m3

8.2 Exposure controls

Appropriate engineering controls

Fresh air (open windows and doors) is necessary..

Personal protection equipment

Eye/face protection

Safety glasses

Hand protection

Hand protection

In Splash contact

Glove material : Butyl rubber

Glove thickness :0,7 mm

Break through time : >120 minute

The protective gloves to be used must comply with the specifications of directive 89/686/EEC and the related standart EN374.

Other skin protection

Flame reterdant antistatic protective chlothing.

Respiratory protection

Required when vapors are generated.


Recommended filter type: A filter (according to DIN 3181), for vapors of organic compounds.

SECTION 9: Physical and chemical Properties

9.1 Information on basic physical and chemical properties



Tekkim is accredited to
ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an  group company
www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Caddesi 8.Sokak No:1 Nilüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

+90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

TEKKİM

Revision Date: 04.08.2022

Version 2

Physical state	Liquid
Colour	Transparent
Odour	No information.
Odour threshold	No information.
pH value	No information.
Melting point/freezing point	No information.
Freezing point	No information.
Initial boiling point and boiling range	No information.
Flash point	-4 °C
Evaporation rate	No information.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	2,2 %(V)
Upper/lower flammability or explosive limits	No information.
Vapour pressure	No information.
Vapour density	No information.
Density	0,90 g/cm ³ 20 °C
Relative density	No information.
Water solubility (g/l)	No information.
Fat solubility (g/l)	No information.
Partition coefficient: n-octanol/water	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	
Kinematic viscosity	No information.
Dynamic viscosity	No information.
Explosive properties	Not classified as explosive.
Oxidising properties	No information.

SECTION 10: Stability and Reactivity

10.1 Reactivity

Vapours may form explosive mixtures with air. Section 10.3 to see.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

Risk of explosion or formation of flammable gases or vapors and exothermic reaction with fluorine, chlorosulfonic acid, strong oxidizing agents, odorous sulfuric acid.

There is a risk of explosion with lithium aluminum hydride, alkali metals, hydrides, alkaline earth metals.

Violent reactions possible with strong acids and strong bases.

10.4 Conditions to avoid

In case of warming.

10.5 Incompatible materials

Rubber, various plastics.

10.6 Hazardous decomposition products


No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1 Information on toxicological effects



Tekkim is accredited to
ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an  group company
www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Caddesi 8.Sokak No:1 Nilüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

+90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

TEKKİM

Revision Date: 04.08.2022 Version 2

Acute oral toxicity
LD50 Rat: 5,620 mg/kg
(RTECS)

Acute dermal toxicity
LD50 Dermal - Rabbit - male - > 20.000 mg/kg
(ECHA)

Serious eye damage/eye irritation
Eyes - Rabbit
Result: slight irritation
(OECD Test Guideline 405)

Carcinogenicity
This product is or contains an ingredient that cannot be classified for carcinogenicity according to IARC, ACGIH, NTP or EPA classification.

Specific Target Organ Toxicity – Single exposure
May cause drowsiness or dizziness. - central nervous system

11.2 Additional information

In high concentrations: Headache, drowsiness, dizziness, vomiting, narcosis, anaemia, central nervous system depression.
Handle in accordance with safety and hygiene rules.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish
flow-through test LC50 - Pimephales promelas (Carp calf) - 230 mg/l - 96 h
(US-EPA)

Toxicity to algae (algae)
static test NOEC - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h
(OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability
Oxygenated (aerobic) - Exposure time 20 d
Result: approx. 69% - Easily degradable.
(ECHA)

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB.

12.6 Other adverse effects

Discharge into environment must be avoided

SECTION 13: Disposal considerations

Waste treatment methods

It must be disposed of in accordance with national and local regulations. Do not mix with other products. Uncleaned Treat packages as if it were the product itself ... Waste materials must be disposed of in accordance with national and local regulations.

SECTION 14: Transport information

ADR	IMDG	IATA	ADN	RID
-----	------	------	-----	-----

14.1 UN number



Tekkim is accredited to
ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an group company
www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nilüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

+90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

TEKKİM

Revision Date: 04.08.2022 Version 2

UN 1173

UN 1173

UN 1173

UN 1173

UN 1173

14.2 UN proper shipping name

ETHYL ACETATE

ETHYL ACETATE

ETHYL ACETATE

ETHYL ACETATE

ETHYL ACETATE

14.3 Transport hazard class(es)

3

3

3

3

3



14.4 Packing group

II

II

II

II

II

14.5 Environmental hazards

NO

NO

NO

NO

NO

No information available.

No information available.

No information available.

No information available.

No information available.

14.6 Special Precautions for User:

No information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental legislation specific for the substance or mixture

This product safety data sheet complies with the requirements of EU Regulation 1907/2006.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been conducted for this substance.

SECTION 16: Other informations

Full text of H statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Person Who Prepared the Safety Data Sheet:

Name:

Erhan DİLER

Certificate Number and Date:


11.29.03 & 11 Şubat 2020

Communication information:

05069903686



Tekkim is accredited to
ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an  group company
www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nilüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

+90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31