Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Revision Date: 26.09.2022 Version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalog No.TK.911014.00000Product NameEthyl Acetate %99,5Cas no141-78-61.2 Relevant identified uses of the substance or mixture and uses

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial use. Use as a laboratory reagent.

1.2.2. Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Name	TEKKİM KİMYA SAN. TİC. LTD. ŞTİ.
Street	ORGANİZE SAN. BÖL. MAVİ CAD. 8. SOK. NO :1 NİLÜFER / BURSA
Telephone	0224 243 21 71
E-mail	erhan@tekkim.com.tr
Company Representative	Erhan DİLER

1.4 Emergency Telephone Number +90 506 990 36 86

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Flammable liquid category 2 Eye irritation category 2 Specific Target Organ Toxicity - Single exposure (Category 1), Central nervous system

For the full text of the H and EUH statements referred to in this section, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 (CLP) Hazard pictograms



Signal word (SEA) DANGER

Hazard Statements (SEA)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements (SEA)

Prevention

- P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.
- P233 Keep container tightly closed.
- P240 Ground/connect container or receiving equipment.
- P241 Use explosion-proof electrical/ventilation/igniter/.../ material.
- P242 Use only non-flammable tools.

Intervention

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if fitted and easy to do. Continue rinsing.





Tekkim is accredited to SO 9001:2015 and ISO 14001:2015

 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Revision Date: 26.09.2022 Version 2

Give up to two glasses of water. Get medical help immediately.

теккім

and

SECTION 3: Composition/information on ingredients

Classification according to Regulation (EC) No. 1272/2008 (CLP)

3.1 Maddeler

EC No	205-500-4	
Molar mass	88.11 g/mol	
Cas No	141-78-6	
Concentration	(<= 100 %)	

SECTION 4: First aid measures

4.1 Description of first aid measures	
General information	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Following inhalation	Remove casualty to fresh air and keep warm and at rest
Following skin contact	Wash with plenty of water. Take off contaminated clothing.
Following eye contact	In case of contact with eyes, rinse immediately with plenty of water an consult an ophthalmologist.

Following ingestion

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

There is no restriction for this item.

5.2 Special hazards arising from the substance or mixture

Carbon oxides. Flammable. Heavy vapors in the air at the ground surface may occur. It can create explosive mixtures with air on intense heating. In case of fire hazardous combustion gases or vapors may occur. Flashback. Caution.

5.3 Advice for firefighters

Special protective equipment for firefighters In case of fire: Wear self-contained breathing apparatus..

5.4 Additional information

Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Don't breathe vapours, aerosols. Avoid substance contact. Keep away from head and source of ignition. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

6.2 Environmental precautions

Be careful not to mix into the sewer. Risk of explosion.

6.3 Methods and material for containment and cleaning up

Close drainage channels. Take up with liquid-absorbent material. Clean the affected area.

6.4 Reference to other sections

Disposal: see section 13.





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

6.5 Additional information

Clear spills immediately.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Advices on safe handling

Observe label precautions. Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advices on general occupational hygiene

Change contaminated clothing. Wash hands after working with substance. It is recommended to use a skin protection cream

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

0 4 0 · · · 4 · · · 1 · · · · ·

Keep container tightly closed in dry and well-ventilated places. Protect from light. Keep away from heat and anything that can cause ignition.

7.3 Specific end uses

There are no other specific uses other than those mentioned in section 1.2.

SECTION 8: Exposure controls / personal protection

Ethyl acetate	(141-78-6)			
TR MAK	Time Weighted Average (TWA):	400 mbp 1.400 mg / m3		

8.2 Exposure controls

Appropriate engineering controls

.

More attention should be paid to technical measures against the use of personal protective equipment.

Personal protection equipment

Eye/face protection Safety glasses Hand protection

Hand protection

In Splash contact Glove material : Butyl rubber Glove thickness :0,7 mm Break through time : >120 minute

The protective gloves to be used must comply with the specifications of directive 89/686/EEC and the related standart EN374.

Other skin protection

Flame reterdant antistatic protective chlothing.

Respiratory protection

Required when vapors are generated. Recommended filter type: A filter (according to DIN 3181), for vapors of organic compounds.

SECTION 9: Physical and chemical Properties

9.1 Information on basic physical and chemical properties





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015



Revision Date: 26.09.2022 Version 2

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Physical state Colour Odour Odour threshold pH value Melting point/freezing point Freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Upper/lower flammability or explosive limits Upper/lower flammability or explosive limits Vapour pressure Vapour density Density Relative density Water solubility (g/l) Fat solubility (q/l) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature

Viscosity

Kinematic viscosity Dynamic viscosity Explosive properties Oxidising properties No information. No information. Not classified as explosive. No information.

SECTION 10: Stability and Reactivity

10.1 Reactivity

Vapours may form explosive mixtures with air. Section 10.3 to see.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

Risk of explosion or formation of flammable gases or vapors and exothermic reaction with fluorine, chlorosulfonic acid, strong oxidizing agents, odorous sulfuric acid.

There is a risk of explosion with lithium aluminum hydride, alkali metals, hydrides, alkaline earth metals. Violent reactions possible with strong acids and strong bases.

10.4 Conditions to avoid

In case of warming.

10.5 Incompatible materials

Rubber, various plastics.

10.6 Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1 Information on toxicological effects





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015
 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31



Version 2

Revision Date: 26.09.2022

Liquid

-4 °C

2.2 %(V)

Transparent No information.

No information.

No information.

No information.

No information.

No information.

No information.

Not applicable.

No information. No information.

No information.

No information.

No information. No information.

No information.

No information.

No information.

0,90 g/cm3 20 °C

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Revision Date: 26.09.2022 Version 2

Acute oral toxicity LD50 Rat: 5,620 mg/kg (RTECS)

Acute dermal toxicity LD50 Dermal - Rabbit - male - > 20.000 mg/kg (ECHA)

Serious eye damage/eye irritation Eyes - Rabbit Result: slight irritation (OECD Test Guideline 405)

Carcinogenicity

This product is or contains an ingredient that cannot be classified for carcinogenicity according to IARC, ACGIH, NTP or EPA classification.

Specific Target Organ Toxicity – Single exposure May cause drowsiness or dizziness. - central nervous system

11.2 Additional information

In high concentrations: Headache, drowsiness, dizziness, vomiting, narcosis, anaemia, central nervous system depression.

Handle in accordance with safety and hygiene rules.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (Carp calf) - 230 mg/l - 96 h (US-EPA)

Toxicity to algae (algae) static test NOEC - Desmodesmus subspicatus (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability Oxygenated (aerobic) - Exposure time 20 d Result: approx. 69% - Easily degradable. (ECHA)

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB.

12.6 Other adverse effects

Discharge into environment must be avoided

SECTION 13: Disposal considerations

Waste treatment methods

It must be disposed of in accordance with national and local regulations. Do not mix with other products. Uncleaned Treat packages as if it were the product itself ... Waste materials must be disposed of in accordance with national and local regulations.

SECTION 14: Transport information				
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1 UN number				





Tekkim is accredited to SO 9001:2015 and ISO 14001:2015

 Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

 Factory:
 0.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

 +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66


 Factory:
 istoc 33.ada No: 47-49-51-53

 +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31

Safety Data Sheet according to Regulation (EC) No. 1907/2006



(REACH) Revision Date: 26.09.2022 Version 2				
UN 1173	UN 1173	UN 1173	UN 1173	UN 1173
14.2 UN proper shipp	oing name			
ETHYL ACETATE	ETHYL ACETATE	ETHYL ACETATE	ETHYL ACETATE	ETHYL ACETATE



14.5 Environmental hazards

NO	NO	NO	NO	NO
No information available.	No information available.	No information available.	No information available.	No information available.

14.6 Special Precautions for User:

No information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental legislation specific for the substance or mixture

This product safety data sheet complies with the requirements of EU Regulation 1907/2006.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been conducted for this substance.

ECHNIC

SECTION 16: Other informations

Full text of H statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Person Who Prepared the Safety Data Sheet:

Name: Certificate Number and Date: Communication information:

Erhan DİLER 11.29.03 & 11 Şubat 2020 05069903686



Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an 🔣 group company www.tekkim.com.tr | tekkim@tekkim.com.tr ISO 14001:2015

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY L +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66 Factory: istoc 33.ada No: 47-49-51-53 L +90 212 659 64 24 (pbx) | Fax: +90 212 659 64 30 - 31