Safety Data Sheet according to Regulation (EC) No. 1907/2006 (RFACH)



Revision Date: 29.09.2022 Version 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Catalog No. TK.911130.00000
Product Name Diethyl Ether
Cas no 60-29-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial use. Use as a laboratory reagent.

1.2.2. Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Name TEKKİM KİMYA SAN. TİC. LTD. STİ.

Street ORGANİZE SAN. BÖL. MAVİ CAD. 8. SOK. NO :1 NİLÜFER / BURSA

Telephone 0224 243 21 71

E-mail erhan@tekkim.com.tr

Company Representative Erhan DİLER

1.4 Emergency Telephone Number +90 506 990 36 86

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 (CLP)

Flammable liquids, Category 1 Acute toxicity, Oral, Category 4

Specific Target Organ Toxicity - Single exposure, Category 3, Central nervous system

For the full text of the H and EUH statements referred to in this section, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictograms





Signal word (SEA)

DANGER

Hazard Statements (SEA)

H224 Extremely flammable liquid and vapour.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

Precautionary Statements (SEA)

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.

P233 Keep container tightly closed.

P240 Ground/connect container or receiving equipment.

P241 Use explosion-proof electrical/ventilation/igniter/.../ material.

Intervention


P301+P312 IF SWALLOWED: Call 114 POISON CENTER or doctor/physician if you feel unwell.

P403+P233 Store in a well-ventilated area. Keep container tightly closed.

SECTION 3: Composition/information on ingredients







Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

+90 224 243 21 /1 (pbx) | 1 dx. +90 224 242

Factory: istoc 33.ada No: 47-49-51-53

Safety Data Sheet according to Regulation (EC) No. 1907/2006





Classification according to Regulation (EC) No. 1272/2008 (CLP)

3.1 Maddeler

200-467-2 EC No 74.12 g/mol Molar mass Cas No 60-29-7 Concentration (<=100%)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information In case of accident or unwellness, seek medical advice immediately

(show directions for use or safety data sheet if possible).

Remove casualty to fresh air and keep warm and at rest.. Following inhalation Following skin contact Wash with plenty of water. Take off contaminated clothing.

Following eye contact Rinse carefully and thoroughly with eye wash or water.

Please give up to two glasses of water. Get immediate medical attention. Following ingestion

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

There is no restriction for this item.

5.2 Special hazards arising from the substance or mixture

Flammable. Heavy-than-air vapors may form on the floor surface. May form explosive mixture with air at intense temperatures. In case of fire, dangerous flammable gases or vapors may develop. There may be glare. Attention please.

5.3 Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus...

5.4 Additional information

Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Don't breathe vapours, aerosols. Avoid substance contact. Keep away from head and source of ignition. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert..

6.2 Environmental precautions

Do not discharge into sewer. Risk of explosion.

6.3 Methods and material for containment and cleaning up

Close drainage channels. Take up with liquid-absorbent material. Clean the affected area.

6.4 Reference to other sections


Disposal: see section 13.

6.5 Additional information

Clear spills immediately.







Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimva Sanavi ve Ticaret Limited Sirketi Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

Safety Data Sheet according to Regulation (EC) No. 1907/2006



Revision Date: 29.09.2022 Version 2

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Advices on safe handling

Observe label precautions. Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advices on general occupational hygiene

Change contaminated clothing. Wash hands after working with substance. It is recommended to use a skin protection cream.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in dry and well-ventilated places. Protect from light. Keep away from heat and anything that can cause ignition.

7.3 Specific end uses

There are no other specific uses other than those mentioned in section 1.2.

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Diethylether (60-29-7)

TR MAK Acceptable 400 mbp

> maximum 1,200 mg / m3

concentration (MAK)

TR OEL Another time 200 mbp

unless specified, 15 616 mg / m3

for a minute

not to be exceeded upper limit of exposure

value (STEL):

8 hour set 100 mbp for reference time 308 mg/m3

measured or calculated time weighted average

(TWA)

8.2 Exposure controls

Appropriate engineering controls

More attention should be paid to technical measures against the use of personal protective equipment.

Personal protection equipment

Eye/face protection

Safety glasses

Hand protection

Hand protection

Splash contact

Glove material: Viton (R) Glove thickness :0,70 mm

Break through time: > 30 minute

The protective gloves to be used must comply with the specifications of directive 89/686/EEC and the related standart EN374.

Other skin protection







Tekkim Kimya Sanayi ve Ticaret Limited Şirketi Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Revision Date: 29.09.2022 Version 2



Flame reterdant antistatic protective chlothing.

Respiratory protection

Required when vapors are generated. Recommended filter type: AX (EN 371)

SECTION 9: Physical and chemical Properties

9.1 Information on basic physical and chemical properties

Physical state Liquid
Colour Transparent
Odour Characteristic
Odour threshold No information.
pH value No information.

Melting point/freezing point -116 °C

Freezing point No information.

Initial boiling point and boiling range 34,6 °C 1.013 hPa

Flash point -40 °C

Evaporation rate No information.

Flammability (solid, gas)

Upper/lower flammability or explosive limits

1,7 % (V)

Upper/lower flammability or explosive limits 36 %(V)
Vapour pressure 587 hPa 20 °C
Vapour density No information.

Density 0,71 - 0,72 g/cm3 20 °C

 $\begin{array}{lll} \mbox{Relative density} & \mbox{No information.} \\ \mbox{Water solubility (g/l)} & \mbox{68 g/L} & \mbox{20 °C} \\ \mbox{Fat solubility (g/l)} & \mbox{No information.} \\ \end{array}$

Partition coefficient: n-octanol/water log POW: 1,1 Bioacumulation isnot expected.

Auto-ignition temperature No information. Decomposition temperature No information.

Viscosity

Kinematic viscosity

Dynamic viscosity

No information.

0,195 mPa.s 20 °C

Explosive properties

Not classified as explosive.

Oxidising properties None

SECTION 10: Stability and Reactivity

10.1 Reactivity

The formation of peroxides is possible. Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is stable under storage at normal room temperatures. Contains stabilizer: Butyl hydroxytoluene (<0.001 - 0.0009 %)

10.3 Possibility of hazardous reactions

Reacts with air to release peroxide.

10.4 Conditions to avoid

Light. Heat. Air. to temperate. Moisture.

10.5 Incompatible materials

Rubber, various plastics.

10.6 Hazardous decomposition products

Peroxides.

SECTION 11: Toxicological information

11.1 Information on toxicological effects





Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



Acute oral toxicity

LD50 Rat: 1.215 mg/kg (RTECS)

Symptoms: Risk of aspiration with vomiting. Inhalation may cause pulmonary edema and pneumonitis.

Revision Date: 29.09.2022

Version 2

Acute inhalation toxicity

LC50 Inhalation - Mouse - 4 h - 97.5 mg/l (RTECS)

Symptoms: mucosal irritations

Acute dermal toxicity

LD50 Rabbit: > 20,000 mg/kg

(ECHA)

Skin irritation

Rabbit

Result: No irritation.

OECD Test Guideline 404 Dermatitis, skin burning

Repeated exposure may cause skin dryness and cracking.

Specific Target Organ Toxicity - Single exposure

May cause drowsiness or dizziness. Target Organs: Central nervous system

11.2 Additional information

If inhaled

Cough, chest pain, difficulty breathing, dizziness, drowsiness.

In case of contact with eyes:

Redness, tearing, blurred vision.

Prolonged or repeated exposure of the skin causes dryness and inflammation of the skin.

Handle in accordance with safety and hygiene rules.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

LC50 Leuciscus idus (Golden orpheus): 2,840 mg/l; 48 hours

(ECOTOX Database)

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 1,380 mg/l; 48 hours

(IUCLID)

Toxicity to algae (algae)

static test EC50 Desmodesmus subspicatus (green algae): > 100 mg/l; 72 hours

OECD Test Guideline 201

Toxicity to bacteria

static test EC50 active waste: 21,000 mg/l; 3 hours

OECD Test Guideline OECD 209

Static test NOEC active waste: 42 mg/l; 3 hours

OECD Test Guideline OECD 209

12.2 Persistence and degradability

It does not dissolve easily in nature by itself.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil


No information available.

12.5 Results of PBT and vPvB assessment

Substance does not meet the criteria for PBT or vPvB.







Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr

Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY

+90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

Factory: istoc 33.ada No: 47-49-51-53

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)



IO C Other adverse affects

12.6 Other adverse effects

Discharge into environment must be avoided.

SECTION 13: Disposal considerations

Waste treatment methods

It must be disposed of in accordance with national and local regulations. Do not mix with other products. Uncleaned Treat packages as if it were the product itself ... Waste materials must be disposed of in accordance with national and local regulations.

Revision Date: 29.09.2022

Version 2

	IMPO	LATA	ADN	DID	
ADR	IMDG	IATA	ADN	RID	
14.1 UN number					
UN 1155	UN 1155	UN 1155	UN 1155	UN 1155	
14.2 UN proper s	hipping name				
Diethyl ether	Diethyl ether	Diethyl ether	Diethyl ether	Diethyl ether	

14.3 Transport hazard class(es)

3 3 3





14.4 Packing group

14.5 Environmental hazards

NO NO NO NO NO

No information available. No information available. No information available. No information available. No information available.

14.6 Special Precautions for User:

No information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental legislation specific for the substance or mixture

This product safety data sheet complies with the requirements of EU Regulation 1907/2006.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been conducted for this substance.

SECTION 16: Other informations

Full text of H statements

H224 Extremely flammable liquid and vapour.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

Person Who Prepared the Safety Data Sheet:

Name:

Certificate Number and Date:

Communication information: 11.29.03 & 11 Şubat 2020

05069903686







Tekkim is accredited to ISO 9001:2015 and ISO 14001:2015

Tekkim Kimya Company is an K group company www.tekkim.com.tr | tekkim@tekkim.com.tr Tekkim Kimya Sanayi ve Ticaret Limited Şirketi

Factory: O.S.B Mavi Cadde 8.Sokak No:1 Nlüfer - BURSA | TURKEY +90 224 243 21 71 (pbx) | Fax: +90 224 242 97 66

+30 224 243 21 71 (pbx) | 18x. +30 224 242 37 0

Factory: istoc 33.ada No: 47-49-51-53